



**HACO-ATLANTIC, Inc.**  
**DBA ATLANTIC MACHINE TOOLS, Inc.**  
**Manufacturers of Sheet Metal Working Machinery**



## SRM 150-10-8

HACO "SYNCHROMASTER" HYDRAULIC PRESSBRAKE

### SPECIFICATIONS

Tonnage . . . . .	150 tons
Capacity . . . . .	150 tons
Overall Bending Length . . . . .	122"
Clear Distance Between Housings . . . . .	102"
Maximum Stroke (Programmable). . . . .	7.8"
Throat . . . . .	9.8"
Open Height . . . . .	15.7"
H.P. Electric Motor . . . . .	20 HP
Voltage . . . . .	220/440 VAC
Rapid Approach Speed . . . . .	165"/min
Maximum Press Speed (Programmable) . . . . .	24"/min
Rapid Return Speed . . . . .	189"/min
Length . . . . .	138"
Overall Height . . . . .	101"
Front/Back . . . . .	67"
Weight . . . . .	17,200 lbs

**Includes Fastbend (2D Windows) Graphics CNC Control, CNC Anti-deflection table, Heavy duty R-axis, Combination European-USA quick clamping manual top toolholders, European bottom clamping holders and safety cages on cylinders and safety backdoor of the brake.**

All HACO-ATLANTIC "SYNCHROMASTER" pressbrakes are built to conform to ANSI B11.3 "American National Standard for machine tools - power press brakes - safety requirements for construction, care, and use". The purchaser shall be responsible for the proper installation and continued use of point of operation guards and/or awareness barriers to assure required operator safety. Haco-Atlantic, Inc. recommends to check out your local safety regulations by OSHA. Haco- Atlantic, Inc. offers optional safety equipment such as two-hand control and light curtains.

Haco-Atlantic, Inc. reserves the right to change any specifications and prices without prior notice and reserves the right to correct any clerical and typographical errors.