



**HACO-ATLANTIC, Inc.**  
**DBA ATLANTIC MACHINE TOOLS, Inc.**  
**Manufacturers of Sheet Metal Working Machinery**



## PPES 135-10-8

HACO "SYNCHROMASTER" HYDRAULIC PRESSBRAKE

### SPECIFICATIONS

Tonnage . . . . .	135 tons
Capacity . . . . .	135 tons
Overall Bending Length . . . . .	122"
Clear Distance Between Housings . . . . .	102"
Maximum Stroke (Programmable). . . . .	7.8"
Throat . . . . .	9.8"
Open Height . . . . .	15.7"
H.P. Electric Motor . . . . .	20 HP
Voltage . . . . .	220/440 VAC
Rapid Approach Speed . . . . .	165"/min
Maximum Press Speed (Programmable) . . . . .	24"/min
Rapid Return Speed . . . . .	189"/min
Length . . . . .	138"
Overall Height. . . . .	101"
Front/Back . . . . .	67"
Weight. . . . .	17,200 lbs

**The machine is equipped with ATS 590 Graphics 2D CNC Control, Amada top toolholders with quick clamp handles and European bottom clamping holders. Cylinders are resealed, fresh oil and filters and repainted. 3 months parts warranty included!**

All HACO-ATLANTIC "SYNCHROMASTER" pressbrakes are built to conform to ANSI B11.3 "American National Standard for machine tools - power press brakes - safety requirements for construction, care, and use". The purchaser shall be responsible for the proper installation and continued use of point of operation guards and/or awareness barriers to assure required operator safety. Haco- Atlantic, Inc. recommends to check out your local safety regulations by OSHA. Haco- Atlantic, Inc. offers optional safety equipment such as two-hand control and light curtains.

Haco-Atlantic, Inc. reserves the right to change any specifications and prices without prior notice and reserves the right to correct any clerical and typographical errors.



